



# SKYCO

SKYLIGHTS

949-629-4090

FRAME FINISH

G90 GALVANIZED

FUSIBLE LINK TEMP. OPTIONS

165° UL/FM    286° UL/FM    OTHER

212° UL/FM    370° UL/FM   \_\_\_\_\_

MANUAL RELEASE OPTIONS

INSIDE RELEASE

BOTH

OUTSIDE RELEASE

- 1) G.I. STEEL LID
- 2) 1"THK. RIGID INSULATION
- 3) EXTERIOR MANUAL RELEASE SHOWN
- 4) G.I. STEEL 12" SELF FLASHING FRAME
- 5) EYEBOLT & PULLEY ASSEMBLY
- 6) LIFTING SHOCK
- 7) LATCH ASSEMBLY
- 8) OPEN EYE TURNBUCKLE
- 9) G.I. STEEL GUTTER
- 10) STRIKER ASSEMBLY
- 11) RIGID INSULATION
- 12) G.I. STEEL HINGE ASSEMBLY
- 13) LOWER SHOCK BRACKET
- 14) 0.080" TENSION SPRING
- 15) FUSIBLE LINK - SPECIFY TEMP
- 16) 0.060" 7 STRAND STEEL CABLE
- 17) G.I. STEEL SHOCK LOCK CHANNEL
- 18) G.I. STEEL DOME FRAME
- 19) EPDM BULB GASKET
- 20) CURB ANCHOR AS REQUIRED @ 12"o.c.

**MODEL: S-ULSV-SF-ML-INS**

SCALE : 1 1/2" = 1'-0"

COMPLIES WITH UL 793

MODEL	INSIDE CURB DIM.	QTY.
4848	48" x 48"	
6060	60" x 60"	
4896	48" x 96"	

**UL INSULATED SELF FLASHING STEEL FRAME DUAL METAL LID SMOKE VENT**

UL LISTING #:

E472388

UL 10 PSF

PROJECT:

PROJECT ADDRESS:

APPROVED BY:

DATE:

CUSTOMER:

CUSTOMER PHONE:

REV. #

JOB #

DATE:

DRAWING #:

SKUL-004-I